

# Trimax Kolormax



## TECHNICAL DATASHEET

[www.ja-int.com](http://www.ja-int.com)

### APPLICATION

Temperature (°C): 140-60°C  
Time: 10-12 seconds  
Pressure: Medium  
Carrier Release: Hot peel

42.7 - 56.9 psi / 2.9 - 3.9 bar / 3.0 - 4.0 kg/cm<sup>2</sup>  
28.4 - 42.7 psi / 2.0 - 2.9 bar / 2.0 - 3.0 kg/cm<sup>2</sup>

### LAUNDERING

Suitable for domestic wash up to 60°C with fabric softener, tumble dry finish, 30 processes.

This product is not suitable for dry-cleaning, and it cannot withstand bleach. This must be ironed on the reverse.

### STORAGE

Store in a cool dry environment away from direct sunlight  
Keep away from direct sunlight

### COMPOSITION

Carrier: Coated Polyester Sheeting  
Ink: Digital & Water Based  
Adhesive: Polyester

### HEALTH & SAFETY

This product is identified as Non-Hazardous to the end user  
No personal protection equipment is required in handling and storage

### ENVIRONMENTAL / RECYCLING

Polyester carrier: Non-recyclable  
Vegan-Friendly: No  
All inks: Compostable

### CERTIFICATION

OEKO-TEX® STANDARD 100  
Flame Retardant: EN ISO 11611 & EN ISO 11612  
Anti-Static: BS EN 1149-5