



J&A (International) Limited
THE GARMENT DECORATION SPECIALISTS

TECHNICAL DATASHEET

Trimax Kolormax



www.ja-int.com | +44 (0)1790 752 757

J&A (International) Ltd. Insignia House, Vale Road, Spilsby, Lincolnshire PE23 5HE

Trimax Kolormax



TECHNICAL DATASHEET

www.ja-int.com

APPLICATION

Temperature (°C):	140-60°C		
Time:	10-12 seconds		
Carrier Release:	Hot peel		
Pressure:	Medium		
High:	56.8 - 71.1 Psi	3.9 - 4.9 Bar	4.0 - 5.0 Kg/Cm2
Medium:	42.6 - 56.8 Psi	2.9 - 3.9 Bar	3.0 - 4.0 Kg/Cm2
Low:	28.4 - 42.6 Psi	2.0 - 3.9 Bar	2.0 - 3.0 Kg/Cm2

COMPOSITION

Carrier:	Coated Polyester Sheeting
Ink:	Digital & Water Based
Adhesive:	Polyester

ENVIRONMENTAL / RECYCLING

Polyester carrier:	Non-recyclable
Vegan-Friendly:	No
All inks:	Compostable

CERTIFICATION

Oeko-Tex:	Standard 100 (Class 2)
Flame Retardant:	EN ISO 11611 & EN ISO 11612

LAUNDERING

Suitable for domestic wash up to 60°C with fabric softener, tumble dry finish, 30 processes.

This product is not suitable for dry-cleaning, and it cannot withstand bleach. This must be ironed on the reverse.

STORAGE

Store in a cool dry environment away from direct sunlight

HEALTH & SAFETY

This product is identified as Non-Hazardous to the end user
No personal protection equipment is required in handling and storage